FINANCIAL VIABILITY OF SOLID BIOFUEL GENERATION: A CASE STUDY IN A PELLET FACTORY IN WESTERN PARANÁ

by Jana Publication & Research

Submission date: 18-Jul-2025 12:21PM (UTC+0700)

Submission ID: 2692517239 **File name:** IJAR-52849.docx (57.88K)

Word count: 4325 Character count: 24818

FINANCIAL VIABILITY OF SOLID BIOFUEL GENERATION: A CASE STUDY IN A PELLET FACTORY IN WESTERN PARANÁ

......

Manuscript Info

.....

Manuscript History
Received: xxxxxxxxxxxxxxxxx
Final Accepted: xxxxxxxxxxx
Published: xxxxxxxxxxxxxx

Key words:-

Rey words:-Economic analysis, Forest residues, financial viability, Renewable energy, Wood pellets.

Abstract

The growing demand for renewable and sustainable energy sources is driving the search for economically viable alternatives, such as wood pellet production. This article presents an economic analysis of a factory located in western Paraná, aiming to assess the financial viability of pellet production from wood residues, especially pine shavings and sawdust. To this end, fixed and variable costs were identified and quantified, the unit production cost per ton was calculated, the market selling price was analyzed, and a discounted cash flow forecast was prepared over 25 years. The data were obtained through a technical visit, an interview with the owner, and a survey of the assets and inputs us 1 in the production process. The results indicated that the average production cost was R\$759.48 per ton, with raw materials being the main component of the variable cost (46%). The economic analysis demonstrated a Net Present Value (NPV) of R\$6,582,427.07, an Internal Rate of Return (IRR) of 22.36%, a discounted payback period of 8 years and 1 month, and a Benefit-Cost Ratio (BCI) of 1.12. It is concluded that wood pellet production is economically viable, especially after the stabilization of industrial operations. The study highlights the activity's potential as a strategy for valorizing forestry residues and diversifying the energy matrix, reinforcing the importance of logistical and energy efficiency improvements to maximize long-term results.

Copy Right, IJAR, 2019,. All rights reserved.

Introduction:

As a renewable source, biomass becomes an alternative worthy of study. Couto¹ states that the use of forest biomass proves viable, both economically and ecologically. Furthermore, Brand² describes that social gains arise from the emergence of companies in the bioenergy sector, which utilize forest residues, thus generating jobs. The use of forest residues to produce pellets, briquettes, and other materials provides environmental benefits, including improved air quality in industrial sites and increased yard and/or warehouse space, as solids do not accumulate in the industrial yard. It also presents the advantage of being linked to the sale of carbon credits and the generation of energy from waste, both of which generate revenue. The World Bioenergy Association³ estimates that global wood pellet production reached 44.3 million tons in 2021, highlighting Europe as the Breest producer, with a 56% share, followed by the Americas with 30%. Furthermore, Mordor Intelligence⁴ reports that the global wood pellet market is expected to reach US\$16.75 billion by 2027, with a Compound Annual Growth Rate (CAGR) of 7.28% from 2022 to 2027.

Brazil, in turn, stands out due to its potential to produce over 298 million tons/year of lignocellulosic residues from the processing of sugarcane, corn, soybeans, and wheat; and 6 million tons of residues generated by the harvesting of eucalyptus and pine⁵. Furthermore, the Brazilian Association of Biomass Pellet and Briquette Industries (ABIB)⁶ reports that: "The generation of mechanically processed wood waste in Brazil was equivalent to 50,778,566.33 m³, a value corresponding to a 45% loss in log processing. The region with the highest waste generation was the South with 21,188,983.25 m³ (41.7%), Southeast (32%), and North (15.3%)".

According to Brainer⁷, in 2021, countries such as Brazil, the United States, China, India, Indonesia, the Russian Federation, and the Eurozone, which are wood pellet producers, improved their performance due to Gross Domestic

Product (GDP) growth. However, regarding pellet consumption, the Brazilian market remains insignificant, despite presenting conditions for growth, due to its excellent climate and soil conditions, as well as its large territorial area. In this context, studies on the use of renewable sources for various economic sectors are essential. To implement new energy generation sources, Pereira points out that aspects related to environmental preservation, the availability and quality of raw materials, as well as the means of production, storage, forms of use, market, and existing technologies must be taken into consideration.

Furthermore, research such as that by Sartori⁹, which analyzes the Brazilian pellet industry with a view to commercializing products in domestic and international markets, is essential. The study, conducted at a company located in southern Brazil, showed favorable results to produce solid wood pellets from reforested areas, thus creating an opportunity for diversifying the Brazilian energy matrix and/or exporting products to other countries. Given this scenario, the study proposes to analyze the economic viability of producing wood pellets manufactured by a company located in Western Paraná.

Literature Review:

This section briefly presents the factors that influence the supply and demand of biomass for energy generation, with an emphasis on the production of wood pellets.

Supply and Demand of Biomass for Energy Generation

Globally, in 2018, approximately 55% of wood biomass consumed was firewood or charcoal, used for cooking or heating homes, mainly in developing countries, where biomass is burned inefficiently, without fully utilizing the heat generated. Regarding Europe's energy matrix, an increase in the consumption of solid biomass was observed, which generally consists of wood—pellets, chips, briquettes, among others. Pellets are particularly theorethy, as they are the largest consumer and importer in the world ¹⁰. Diniz ¹¹ presents a study that highlights the largest countries in production, import, export, and apparent consumption of forest products for energy (FPE): China, India, Brazil, the United States, Ethiopia, Congo, Nigeria, Ghana, Uganda, and Indonesia. In 2020, they produced 1.3 billion cubic meters, representing approximately 52% of the global market. However, looking at 2020, Brazil is not ranked among the top countries in terms of FPE exports, due to production (175.32 million cubic meters) being practically ¹² all to apparent consumption (173.44 million cubic meters).

However, the Food and Agricu¹²e Organization of the United Nations ¹² reports that Brazilian pellet exports increased by approximately 90% in 2021 compared to the previous year.

Furthermore, regarding the production of PFE by categories in 2020, the following countries stand out in the world market: India (302.24 million m3 of firew 16, Brazil (18.21 million m3 of charcoal), China (44.38 million m3 of chips and 104 million m3 of wood waste), and the United States of America (USA, 11.60 million m3 of pellets)¹¹. However, in 2020, due to the pandemic, there was a reduction in the global consumption of practically all forest products, except for paper, pellets, and other agglomerates⁷.

The positive variation of around 0.5% in pellet consumption in 2020 can be justified due to a global change in consumer behavior (they adopted the preventive measure "stay at home", due to Covid-19), who used pellets as thermal and/or electrical energy for residential heating, in plants and industries (with emphasis on food producers)⁷.

Factors Influencing Pellet Production

As companies grow and mature in the production and marketing of wood pellets, competitiveness increases, resulting in reduced profit margins in the production chain and a scenario of insecurity for producers¹³. Due to production expansion (increased output – consequently, reduced unit costs), companies tend to make trade-offs, as large quantities of inputs are required, resulting in increased transportation and logistics costs¹⁴.

The pellet production industry faces factors that influence production costs, such as the availability of raw materials and their quality (type and seasonality), as well as the widely varying prices, transportation and logistics, electricity rates, and, most importantly, the installed capacity of the plant¹⁵. Pereira⁸ describes that for the company to be competitive, it becomes important to optimize these factors, since they directly influence the layout and location of the facilities, in addition to the quality of the products and, mainly, the final production cost.

Furthermore, according to Sartori⁹, for the price and supply of pellets to remain stable (a fundamental condition for the product to be used as an energy resource), the company must analyze the possibility of a raw material shortage, as this represents an increase in production costs and a risk to its continuity.

Furthermore, Fritsche¹³ report that "wood pellet prices (for industrial or residential purposes) are driven by factors such as exchange rate fluctuations, temperature changes throughout the year (for residential use), fuel prices (e.g., oil), and dependence on incentives for the use of renewable energy sources. In addition to these factors, it can be

argued that the deficiency or scarcity of other energy sources can drive pellet consumption in countries that have infrastructure for their use"

Wood Pellet Production Coos

The value-adding process in a wood pellet production chain begins with the acquisition of raw materials (50% - the purchase cost is low, but the initial investment to process it will be high) and ends with the delivery of biofuel to buyers or traders16

Wood pellet production costs (approximately 40%) include fixed costs (the annual depreciation cost of assets required for the plant's operation and operational and maintenance costs) and variable costs (costs for raw materials, electricity, telephone services, packaging, among others)16

A way to reduce wood pellet production costs, as it significantly reduces specific energy consumption. This is achieved by minimizing the amount of wood raw material sent to wet crushing hammer mills, which must undergo preliminary particle size classification. Implementing this measure can significantly reduce specific energy consumption for pellet production 17

In Brazil, logistics remain a challenge for transporting wood pellets, as most are transported by truck, thus adding costs to the final product. Furthermore, when shipping solid biomass abroad, in some situations, the Free on Board (FOB) price may be added.

Methodology:

This study uses an empirical-analytical approach, focusing on the economic evaluation of wood pellet production. Initially, data on fixed and variable costs were collected from the company under study. Subsequently, an economic analysis of the product's production and marketing was conducted.

The scenario analyzed corresponds to a factory located in the Concórdia do Oeste district, Toledo, Paraná, with four years of operation and a 500 m² manufacturing plant. The region is an emerging pellet production hub, with three other companies located in nearby cities, between 100 km and 180 km away.

The analysis was conducted based on the following technical assumptions:

- · The company has no active debt.
- Advertising and marketing were disregarded.
- · The target market is regional.
- Annual inflation assumed: 5.79%¹⁸.
- The conversion efficiency of raw materials into pellets was estimated at 75%, considering losses due to processing
- The maximum distance for transporting raw materials was limited to 150 km, considered economically viable⁸.
- The selling price of pellets in the first two years was set at R\$600/ton, with direct pickup from the factory²⁰.
- The nominal capacity from the fifth year onward was estimated at 5,040 ton/year;
- Sales are made exclusively in bulk, directly to the end consumer, with transportation limited to 100 km;
- It was assumed that the pellets are not intended for export, given the lack of international certifications and formal internal quality controls, in addition to logistical limitations ¹⁶.

Furthermore, land acquisition costs were calculated based on the average value of properties in capacity class A-I in Toledo (R\$ 163,100.00/ha), with an annual appreciation of 13% above inflation21

Transportation and Tax Costs

To estimate annual transportation and tax costs, we considered the transportation of raw materials to the manufacturing plant (FOB freight) and the delivery of pellets to the end consumer (CIF freight). Calculations were based on the equations proposed by Pereira⁸, considering the quantities transported, average freight costs per ton, taxes per kilometer, and distances traveled.

The following logistical assumptions were adopted:

- The raw material is collected entirely by the company, and 100% of production is delivered to the consumer (no on-site pickup).
- Two types of vehicles were used: medium-duty truck (11 ton) and heavy-duty truck (23 ton)²².
- · Maximum distance for raw material collection: 300 km (round trip).
- Maximum distance for final product delivery: 200 km (round trip).
- The average tax rate on freight was 9.57%, depending on the type of vehicle.
 The average freight and tax rates applied were obtained from updated road transportation industry sources^{23,24} (Tables 1 and 2).

Table 1: - Raw material collection logistics

Item	Medium Truck	Heavy Truck
Average freight (R\$/ton)	R\$93.90	R\$44.02
Average tax (R\$/km)	R\$0.33	R\$0.32
Maximum distance (km)	300 (round trip)	300 (round trip)

Table 2: - Pellet Delivery Logistics

Item	Medium Truck	Heavy Truck			
Average freight (R\$/ton)	R\$65.86	R\$31.30			
Average tax (R\$/km)	R\$0.35	R\$0.34			
Maximum distance (km)	200 (round trip)	200 (round trip)			

These parameters allow us to calcul 13 the total logistics costs, which were integrated into the economic analysis of production, contributing to the final cost of wood pellets.

Cost of Pellet Production

The wood pellet production cost analysis was based on the model proposed by Mani²³, considering the fixed and variable costs associated with operating a manufacturing plant. The total fixed cost (C_a) was calculated based on the recovery of capital invested in equipment.

$$C_a = e \times C_eq$$

Where: e: Capital Recovery Factor, given by Equation 4. C_eq: cost of the equipment [R\$].

The capital recovery factor (e) was obtained by Equation:

$$e = (i \times (1+i)^{N}) / ((1+i)^{N} - 1)$$

Where: i: interest rate [%]. N: equipment amortization period [years].

Additionally, installation costs were estimated at 40% of the equipment acquisition value. The useful life of the plant's fixed assets was estimated using technical criteria consistent with the relevant literature¹⁶, considering the following time horizons: 12 years for the pellet mill and dryer/furnace assembly, 10 years for the tractor and administrative furniture and equipment, 20 years for the industrial buildings, and 25 years for the land. These timeframes were used for both straight-line depreciation purposes and for assessing capital replacement over the project's life cycle.

The total annual production $cost(C_T)$ was determined by Equation:

$$C_T = C_a + C_{op}$$

Investment analysis methods

The investment analysis was conducted using the discounted cash flow (DCF) technique, considering annual inflows and outflows over the project horizon. The present value (PV) of future revenues was calculated using Equation²⁴:

$$PV = FV / (1 + i)^n$$

Depreciation was calculated using the straight-line method (cash basis), as per Equation:

$$D_e = (VA - VR) / V_u$$

Where VA: acquisition value, VR: residual value, and V_u: useful life of the asset. The residual value at the end of the useful life was estimated using Equation:

 $VR = Initial\ Value - (D_e \times V_u)$

To assess the economic viability of the project, the Net Present Value (NPV), Internal Rate of Return (IRR), and Benefit-Cost Ratio (BCR) indicators were used:

```
\begin{split} & \text{NPV} = \sum \left( \text{FC\_j} / \left( 1 + \text{MARR} \right)^{j} \right) \\ & 0 = \sum \left( \text{FC\_j} / \left( \frac{5}{5} + \text{MARR} \right)^{j} \right) \\ & \text{BCR} = \sum \left( \text{FC\_j} / \left( 1 + \text{MARR} \right)^{j} \right) / \text{FC}_{0} \end{split}
```

Where FC_j represents the cash flow in year j, FC₀ the initial investment, MARR the minimum attractive rate (12% per year), and n the number periods (25 years). Operating expenses (OPEX) were considered as 1% of the capital invested (CAPEX).

Results and Discussions:

The analysis was conducted using data collected during a technical visit to the plant in western Paraná in January 2023. During the visit, the main fixed and variable assets were identified, as well as the logistical steps involved in acquiring raw materials and distributing the final product. The initial investment reported by the owner was R\$3,270,000.00, later updated to R\$4,955,024.23 based on asset revaluations and an on-site survey.

The plant operates with seven employees working nine hours a day, six days a week, totaling 2,592 hours of annual operation. The raw material consists predominantly of pine shavings and sawdust, obtained from regional sawmills, at an average cost of R\$350.00/ton. Initial production was 576 ton/year, reaching nominal capacity of 5,040 ton/year in the third year of operation. Operating losses, including flaring for internal consumption and waste, accounted for 25% of the total purchased.

Annual variable costs totaled R\$3,293,828.98 in 2022, with raw materials accounting for 63% of this amount. The total fixed cost analysis considered items such as land, buildings, pellet mill, vehicles, dryer, and administrative infrastructure. The data are consolidated in Tables 3, 4, and 5, highlighting the annual capital cost, which reached R\$523,445.04, representing an average unit cost of R\$103.86 per ton produced.

Table 6 presents the detailed cost structure by stage of the production process. Raw materials represent the largest portion (46.08%) of the total unit cost, followed by electricity and fuel costs (18.18%). This breakdown is consistent with data in the literature¹⁶, which reports a cost over 50% reduction in the purchase of wood shavings alone. Energy efficiency and the internal reuse of furnace waste demonstrate potential for reducing operating costs.

Based on the total cost of R\$759.48/ton (excluding transportation), the logistical impact on the final price was assessed. Considering raw material transportation, it was found that the use of heavy-duty trucks reduces the cost to R\$761.75/ton, while medium-duty trucks increase the cost to R\$769.55/ton. For pellet delivery to the consumer, additional freight varies between R\$6,927.68 and R\$30,175.85 per year, depending on the type of vehicle, which significantly impacts the company's profit margin. Including these costs in the final sales price is crucial, especially considering that the pellets are delivered directly to the customer (CIF).

Furthermore, it was observed that some of the residual biomasses are stored outdoors, which can generate future environmental and operational costs. A recommended strategy is the physical and chemical characterization of this waste for eventual reuse, adding value to the process and reducing waste volume. The possibility of increasing the product's value by obtaining ENplus® certification was also highlighted, aiming for market penetration.

Finally, the results indicate that the project's economic viability depends heavily on logistics optimization, efficient management of energy inputs, and reduction of production losses. Full utilization of installed capacity—including the activation of the second pellet mill currently idle—is strategic for reducing fixed costs and increasing the plant's competitiveness in the regional and, potentially, international markets.

Table 3: - Annual quantity of raw material for effective production of wood pellets

	tuble by Thindan quantity of faw material for effective production of wood penets					
	Year	Raw material	Raw material losses	Furnace burning	Pellets produced	
		consumed	(tons/year)	(tons/year)	(tons/year)	
L		(tons/year)				
	1	745.41	37.27	37.27	576	
	2	2,236.24	111.81	111.81	1,728	
Γ	3 a 25	6,523.00	296.50	296.50	5,040	

Table 4: - Structure of annual variable costs related to the production of wood pellets

Г	Item	Description	,	Value (R\$)

Electricity	(12-month cost)	336,000.00
Administrative costs	Salaries and pro-labor, accounting,	263,128.98
	and taxes	
Internet	(12-month cost)	1,200.00
Raw materials	Wood waste	2,075,000.50
Packaging	Packaging for pellet bags	252,000.00
Fuel	Gasoline and diesel	360,000.00
Starch	Binder	6,000.00

Table 5: - Composition of fixed investments applied in the wood pellet production plant

Item	Description	Value (R\$)
Land	Property area	1,973,510.00
Tools	Tooling for equipment operation	30,000.00
	and mantenance	
Vehicles	Car (1 unit), Tractor (1 unit) and	1,080,448.00
	Truck (2 units)	
Pelletizing	Pelletizer (2 units)	990,000.00
Dryer/furnace	Dryer	435,000.00
Factory (construction)	Factory area (500 m ²)	250,000.00
Furniture and computers	Administrative area	15,000.00
Sieve	Equipment	36,000.00
Vehicles	Tractor	150,000.00

Table 6: – Analysis of the composition of the total cost of production of wood pellets by stage of the industrial

Pelletizing Process Steps	Capital Cost	Operating Cost	Total Cost	Cost Distribution
	(R\$/ton)	(R\$/ton)	(R\$/ton)	(%)
Raw material	-	350.00	350.00	46.08
Dryer/furnace	13.93	0.86	14.80	1.95
Vehicles	37.94	2.44	40.38	5.32
Pelletizer	44.40	1.96	46.36	6.10
Sieve	1.26	0.07	1.34	0.18
Bagging	-	50.00	50.00	6.58
Storage	-	1.21	1.21	0.16
Miscellaneous Materials	-	8.93	8.93	1.18
Employees	-	29.32	29.32	3.86
Factory (construction)	6.32	49.60	55.93	7.36
Taxes	-	22.89	22.89	3.01
Electricity	-	66.67	66.67	8.78
Fuel	-	71.43	71.43	9.40
Internet	-	0.24	0.24	0.03

Economic Analysis

The economic evaluation of the project was performed considering the plant's 25-year accounting useful life, with cash flows adjusted to constant currency and depreciation amounts adjusted for inflation. Operating costs remained constant from the third year onward, with variation only in depreciation, given its real decline over time.

Financial Viability Indicators

Depreciation of fixed assets was estimated based on the straight-line method and adjusted 6 inflation, as suggested by Quéno 6, resulting in an average annual cost of R\$40.43 per ton of pellets produced. At the end of the assets' useful life, the estimated residual value corresponds to approximately 20% of the initial investment, totaling R\$617,000.

Considering an average annual production of 5,040 tons of pellets, sold at R\$1,100.00 per ton from the third year onward, annual gross revenue stabilizes at R\$5.54 million. However, from the tenth year onward, a possible

reduction in net revenue is expected due to equipment obsolescence, the need for reinvestment, and increased operating costs, as noted by Orellana (2019).

Based on the projected cash flow and a minimum attractive rate (MAR) of 12% the economic and financial performance indicators indicate a Net Present Value (NPV) of R\$6,582,427.07 and an Internal Rate of Return (IRR) of 22.36%. Because the IRR exceeds the MAR, the investment is existered economically viable. The discounted payback period was estimated at 8 years and 1 month, indicating the time required for a return on the invested capital. In addition, the Benefit-Cost Index (BCI) was 1.12, confirming that the benefits exceed the costs over the analysis horizon, consolidating the economic attractiveness of the project.

mclusion:

This study aimed to assess the economic viability of wood pellet production at a facility located in western Paraná, identifying and measuring fixed and variable costs, calculating the production cost per ton, analyzing the market price, and developing a discounted cash flow over 25 years of operation.

The results show that raw materials represent the largest portion of variable costs (46%), due to the limited local access to wood residues suitable for pellet production. Fixed costs, in turn, are significantly impacted by the acquisition of machinery and manufacted ing infrastructure, particularly the pellet mill and logistics vehicles. The total cost analysis revealed an average production cost of R\$759.48 per ton, excluding freight, a value consistent with the market price in nearby regions.

With production stabilization starting in the third year, annual revenue reach 15 R\$5.54 million, yielding positive economic results Financial indicators corroborate the investment's viability, with a Net Present Value (NPV) of R\$6.582,427.07, an Internal Rate of Return (IRR) of 22.36%, and a discounted payback period of 8 years and 1 month. Furthermore, the Benefit-Cost Ratio (BCI) of 1.12 reinforces the project's attractiveness, indicating a return higher than the opportunity cost of capital.

Therefore, it can be concluded that, under the adopted assumptions, wood pellet production is economically viable and represents promising alternative for adding value to lignocellulosic waste, in addition to contributing to the diversification of the energy matrix with a renewable source. However, it is recommended that energy efficiency strategies be adopted and that supply chain logistics be reassessed to mitigate operating costs and maximize economic gains over time.

Acknowledgments:

VIII Brazilian Forest Service (SFB) Award in Forest Economics and Market Studies.

References

- Couto, L.C.; Abrahão, C. P.; Faria E. R.; Couto, L. M. F. Energy Uses of Plant Biomass. Biomass & Energy Journal, Viçosa, Minas Gerais, v. 5, n. 1, 2012.
- 2. Brand, M. A. et al. Biomass production for energy generation in Pinus taeda L. stands with different ages. Revista Árvore, v. 38, n. 2, p. 353–360, 2014.
- 3. World Bioenergy Association (WBA). Global Bioenergy Statistics 2021. WBA, 2021. Available at: https://www.worldbioenergy.org/global-bioenergy-statistics/.
- 4. Mordor Intelligence. Wood pellet market growth, trends, Covid-19 impact, and forecasts (2023 2028). 2023.
- Available at: https://www.mordorintelligence.com/pt/industry-reports/wood-pellet-market.

 5. Bonassa, G.; Schneider, L.T.; Canever, V.B.; Cremonez, P. A.; Frigo, E. P.; Dieter, J.; Teleken, J. G. Scenarios and prospects of solid biofuel use in Brazil. Renewable and Sustainable Energy Reviews, vol. 82, p. 2365-2378, 2018.
- Brazilian Association of Biomass Pellets and Briquettes Industries and Brazil Biomass and Renewable Energy (ABIBI). National and international situation – biomass pellets and briquettes industrial sector. ABIB, 2019.
- 7. Brainer, M. S. de C. P. Forest Products. ETENE Sector Notebook, year 7, no. 213, Technical Office for Economic Studies of the Northeast ETENE, 2022.
- 8. Pereira, A. S. Use of wood pellets for energy purposes: market research. V SFB Award in Forest Economics and Market Studies, 2019.
- 9. Sartori, R. S. The wood pellet industry for domestic use and export in Brazil. 2022. 119 p. State University of Campinas, 2022.
- 10. Quéno, L. R. M.; et al. Technical aspects of wood pellet production. Forestry Science, Santa Maria, v. 29, n. 3, p. 1478-1489, 2019.

- 11. Diniz, F. F. Eco-efficiency and international market structure for forest products for energy. 2022. 150 p. Federal University of Parafba, 2022.
- 12. Food and Agriculture Organization of the United Nations (FAOSTAT). Forestry Production and Trade. Available at: https://www.fao.org/faostat/en/#data/FO.
- 13. Fritsche, U. R.; et al. Margin potential for a long-term sustainable wood pellet supply chain. Task 40: New Publication, IEA, 2019.
- 14. International Renewable Energy Agency (IRENA). Solid biomass supply for heat and power: Technology brief. International Renewable Energy Agency, Abu Dhabi, 2018.
- 15. Santos, F.; Colodette, J.; Queiroz, J. H. de. Bioenergy and Biorefinery Sugarcane & Forest Species. Federal University of Viçosa, 2013.
- 16. Queno, L.R.M. Wood Pellet Production in Brazil: Strategy, Cost and Investment Risk. 2015. 162 p. University of Brasília, 2015.
- 17. Lyubov, V.K., Popov, A.N., Alekseev, P.D. Efficiency of the Production of Wood Pellet Fuel. Solid Fuel Chem. 56, p. 368–379, 2022. Disponível em: https://doi.org/10.3103/S036152192205007X.
- $18.\ Brazilian\ Institute\ of\ Geography\ and\ Statistics\ (IBGE).\ Inflation.\ Available\ at: https://www.ibge.gov.br/explica/inflacao.php.\ 2023.$
- 19. Serrano, D. M. C. Assessment of the Production and Export Potential of Fuel Pellets in the Forestry Hub of the Southern Region of Brazil. 2009. 83 p. State University of Campinas, 2009.
- 20. Garcia, D. P.; Caraschil, J.C.; Ventorim, G. The wood pellet sector in Brazil. Wood Science Journal, v. 8, n. 1, 2017c. Available at: DOI: 10.12953/2177-6830/rcm.v8n1p21-28.
- 21. Hachmann, F. J. Analysis of the behavior of mechanized land prices in municipalities with the highest volume of soybean, corn, and wheat production in Paraná. 2021. 35p. Federal University of Paraná, 2021.
- 22. Department of Highways (DER). Official weight table 2018 updated 2-2018. DER SP, 2018. Available at: http://www.der.sp.gov.br/WebSite/Arquivos/peso/TABELA_OFICIAL_PESO.pdf.
- 23. Mani, S., Sokhansanj, S., Bi, X., Turhollow, A. Economics of producing fuel pellets from biomass. Applied Engineering in Agriculture, v. 22, n.3, p. 421-426, 2006.
- 24. Baye, M. R. Business Economics and Business Strategies. Publisher: AMGH, 6th ed., 2010.

FINANCIAL VIABILITY OF SOLID BIOFUEL GENERATION: A CASE STUDY IN A PELLET FACTORY IN WESTERN PARANÁ

ORIGINA	ALITY REPORT			
8 SIMILA	% ARITY INDEX	5% INTERNET SOURCES	5% PUBLICATIONS	1% STUDENT PAPERS
PRIMAR	Y SOURCES			
1	Diniz, Jo Fuinhas forest pi	reira Coelho Jur ice Machado Ma et al. "Worldwid roducts for ene Technologies an	artins, José All de concentrat rgy", Sustaina	oerto ion of ble
2	fasterca Internet Source	pital.com		1 %
3	Chaves Andrade "Influencompos use of lig	Bezerra da Silva Arantes, Jaily Ke e, Carlos Rogério ce of physical an itions on the pro gnocellulosic bio Renewable Ener	erller Batista do Andrade et and chemical operties and and some some some some some some some some	e al. energy
4	acervod Internet Source	igital.ufpr.br		1 %
5	Orzáez, Terrado Evaluatio Gasificat Process Decentr	mo-Calado, Mai José La Cal-Heri s-Cepeda. "Tech on of Downdraf tion of Almond Step in Energy alized Solutions	rera, Paulo Br nno-Economic t Fixed Bed Shell and Hus Production fo Applied in Bi	ito, Julio k as a r

7	getd.libs.uga.edu Internet Source	<1%
8	www.marketsandmarkets.com Internet Source	<1%
9	Vahid Nabavi, Majid Azizi, Asghar Tarmian, Charles David Ray. "Feasibility study on the production and consumption of wood pellets in Iran to meet return-on-investment and greenhouse gas emissions targets", Renewable Energy, 2020	<1%
10	ria.utn.edu.ar Internet Source	<1%
11	Submitted to University of Newcastle upon Tyne Student Paper	<1%
12	www.orfonline.org Internet Source	<1%
13	era.library.ualberta.ca Internet Source	<1%
14	www.iisd.org Internet Source	<1%
15	Nestor Proenza Perez, Edilson Adriao Cabral, Thiago Abelardo Bimestre, Carla Almeida Loures et al. "Harnessing Biogas from STPs for Sustainable Energy: A Techno-Economic Study", Springer Science and Business Media LLC, 2024 Publication	<1%
16	landgap.org Internet Source	<1%
17	www.ame.com.tr Internet Source	<1%

Tu, Qingshi, Chao Zhu, and Drew C. McAvoy. "Converting campus waste into renewable energy – A case study for the University of Cincinnati", Waste Management, 2015.

Publication

Exclude quotes

On

Exclude matches

Off

Exclude bibliography