



Journal Homepage: [-www.journalijar.com](http://www.journalijar.com)

## INTERNATIONAL JOURNAL OF ADVANCED RESEARCH (IJAR)

Article DOI:10.21474/IJAR01/24262  
DOI URL: <http://dx.doi.org/10.21474/IJAR01/24262>



### RESEARCH ARTICLE

## SMART ENVIRONMENTAL MONITORING FOR SAUDI MEGA-PROJECTS: INTEGRATING DIGITAL TECHNOLOGIES WITH ENVIRONMENTAL COMPLIANCE

Fazal Ahmed Khan

### Manuscript Info

#### Manuscript History

Received: 16 July 2026

Final Accepted: 18 August 2026

Published: September 2026

#### Key words:-

smart environmental monitoring; Saudi Arabia; Vision 2030; mega-projects; environmental compliance; Internet of Things; digital twin; BIM; artificial intelligence; construction dust; NCEC; ISO 14001

### Abstract

Saudi Arabia's rapid delivery of mega-projects under Vision 2030 is occurring alongside a strengthening environmental compliance regime and an accelerating national digital transformation. This combination creates a practical need to move environmental monitoring beyond periodic sampling and retrospective reporting toward continuous, risk-based and auditable digital oversight. This paper develops a conceptual framework for smart environmental monitoring in Saudi mega-projects by integrating Internet of Things (IoT) sensors, edge computing, Building Information Modelling (BIM), Geographic Information Systems (GIS), digital twins, artificial intelligence (AI), machine learning (ML), unmanned aerial vehicles (UAVs), cloud platforms and secure data-traceability mechanisms with environmental management and regulatory compliance processes. The study uses a structured narrative review of recent peer-reviewed literature and official Saudi sources, including the National Center for Environmental Compliance (NCEC), Vision 2030 reporting and ISO 14001:2026. The synthesis identifies six core requirements for effective implementation: fit-for-purpose sensing, data quality assurance, spatial and operational contextualisation, automated compliance logic, accountable response workflows, and governance of data, cybersecurity and human decision rights. A Smart Environmental Monitoring and Compliance Framework (SEMcF) is proposed for large infrastructure, tourism, transport, urban and industrial developments.

"© 2026 by the Author(s). Published by IJAR under CC BY 4.0. Unrestricted use allowed with credit to the author."

The framework links real-time environmental measurements to permit conditions, risk registers, construction activities, predictive analytics, alerts, corrective actions and regulatory evidence. Particular attention is given to dust and air quality, noise and vibration, water and soil quality, waste and pollution incidents, biodiversity-sensitive areas and cumulative impacts. The paper argues that digital monitoring creates value only when measurement quality, calibration, threshold governance and response accountability are designed as part of the environmental management system rather than added as isolated technology. The framework offers a practical research and implementation agenda for Saudi mega-projects and can be empirically validated through future multi-project case studies, expert assessment and longitudinal monitoring data.

**Introduction:-**

Saudi Arabia is implementing one of the world's most ambitious portfolios of large-scale infrastructure and urban-development projects. Transport systems, tourism destinations, industrial zones, energy developments and new urban districts are being delivered at a scale that places environmental management under sustained operational pressure. At the same time, Vision 2030 has embedded sustainability and digital transformation within the country's development model. The result is a policy environment in which environmental performance is expected to be both demonstrable and increasingly data driven (Saudi Vision 2030, 2026).

Conventional environmental monitoring on construction and infrastructure projects is often periodic. Air, water, soil or noise measurements may be collected according to a schedule, analysed later, and then incorporated into monthly or quarterly reports. Such systems remain necessary, particularly where accredited sampling and laboratory analysis are required, but they can leave a significant visibility gap between sampling events. Construction impacts are dynamic: dust concentrations can change within minutes as wind direction shifts; noise varies with equipment and work sequencing; runoff quality can deteriorate during rainfall or dewatering; and incidents such as fuel spills or uncontrolled discharges can emerge rapidly. A monitoring system that only documents conditions after the event may therefore support reporting without fully supporting prevention.

Saudi environmental regulation is moving toward more technology-enabled oversight. In 2026, NCEC and the Royal Commission for Riyadh City announced construction dust-control requirements for qualifying projects in Riyadh that include installation of air-quality measurement devices, connection to a unified construction-dust monitoring platform and periodic environmental performance reporting. NCEC has also reported a risk-based inspection approach that prioritises activities with higher environmental impact, while its broader environmental-quality mandate covers air, water, soil, coastal environments, noise and light pollution (NCEC, 2026a; NCEC, 2026b; NCEC, n.d.-a). These developments make smart environmental monitoring directly relevant to compliance practice rather than merely a future-oriented technology concept.

Research in construction and the built environment has simultaneously demonstrated the potential of IoT-based particulate monitoring, BIM-integrated sensing, edge computing, predictive modelling, digital twins, UAV-based spatial observation and blockchain-supported data traceability. Kim et al. (2021) developed an IoT particulate-matter monitoring system for construction sites; Xu et al. (2022) integrated BIM, edge computing and prediction models for construction air-pollution management; Guo et al. (2022) combined IoT monitoring with LSTM-based PM<sub>2.5</sub> forecasting; and Zhong et al. (2022) demonstrated a blockchain framework for on-site construction environmental monitoring. Digital twin research has further shown how real-time sensor streams can be spatially and semantically connected to built assets to support environmental interpretation and prediction (Wang et al., 2022; Kang & Mo, 2024).

However, a gap remains between technology demonstrations and a complete compliance operating model for Saudi mega-projects. A sensor network alone does not establish compliance. Measurements must be accurate enough for their intended purpose; sensor location and calibration must be governed; thresholds must reflect permit and regulatory requirements; exceedances must trigger accountable actions; data must be retained with a defensible audit trail; and environmental professionals must remain responsible for interpretation where uncertainty is material. The research problem addressed by this paper is therefore how digital monitoring technologies can be integrated into an environmental management and compliance architecture suitable for large Saudi infrastructure projects.

The paper has four objectives: (1) to synthesise recent evidence on digital environmental monitoring technologies relevant to construction and infrastructure; (2) to interpret these technologies within the Saudi compliance context; (3) to develop a Smart Environmental Monitoring and Compliance Framework (SEMCF); and (4) to identify practical governance, assurance and research requirements for implementation. The contribution is conceptual and implementation-oriented. It does not claim measured performance improvement on a particular Saudi project; instead, it provides a structured framework that can be tested empirically in future project research.

**Saudi Environmental Compliance and Vision 2030 Context:-**

Saudi Vision 2030 links economic transformation with environmental sustainability and digital government. The Vision 2030 Annual Report 2025 describes sustainability as integral to the national transformation and reports strong progress in government digital-transformation maturity. This combination matters for mega-project environmental management because compliance systems increasingly operate within a broader national expectation of measurable performance, digital services and transparent accountability (Saudi Vision 2030, 2026).

NCEC is central to this operating environment. Established in 2020, the Center monitors the compliance of development activities with approved environmental regulations, standards and requirements. Its environmental-quality functions include oversight of monitoring and analysis across air, water, soil, coastal environments, acoustic noise and light pollution. NCEC also operates electronic services for environmental permits and monitoring reports and requires relevant reports and measurements to be prepared or implemented by licensed environmental service providers where applicable (NCEC, n.d.-a; NCEC, 2026c). This means that digital monitoring should not be designed as a parallel technology system outside formal compliance. It should support, and where permitted connect with, the evidence needed for regulatory reporting and environmental management.

Recent developments demonstrate the direction of travel. The 2026 Riyadh construction requirements introduced specific controls for dust-generating activities and require qualifying construction projects to install air-quality monitoring devices and connect them to a unified monitoring platform. The requirement is particularly significant because it converts continuous environmental sensing from an optional innovation into a direct compliance mechanism for certain projects. NCEC also reported more than 11,000 inspection visits in the first quarter of 2026 and described the use of data analysis, air-quality monitoring stations, smart buoys and drones to support risk-focused oversight. These practices indicate a move toward continuous and technology-assisted regulatory intelligence (NCEC, 2026a; NCEC, 2026b).

ISO 14001:2026 provides a complementary management-system foundation. The standard requires organisations to manage environmental responsibilities systematically, meet compliance obligations, monitor environmental performance and pursue continual improvement (ISO, 2026). Smart monitoring can strengthen these functions by reducing the delay between environmental change, detection, interpretation and response. Yet the same standard also reinforces the need for controlled processes, reliable evidence, competent personnel and structured evaluation. Technology must therefore be embedded within an Environmental Management System (EMS), not treated as a substitute for one.

Saudi mega-projects create additional complexity. Their footprints can span large areas and multiple environmental receptors; work packages may involve numerous contractors; construction phases can change rapidly; and interfaces between earthworks, roads, utility corridors, camps, batching plants, crushers, marine works and logistics create many potential emission and pollution sources. A centralised environmental team cannot physically observe every source continuously. Digital systems are valuable precisely because they can extend visibility spatially and temporally, but their architecture must be scalable and capable of distinguishing project-related impacts from background conditions and regional environmental variability.

The compliance opportunity can therefore be stated clearly: use digital monitoring to create a verified chain from environmental condition to management action. This chain begins with sensing, continues through data validation and contextualisation, applies regulatory and project thresholds, triggers proportional action, verifies the outcome and preserves an auditable record. The remainder of this paper develops the technical and governance components needed to operationalise that chain.

### **Digital Technologies for Smart Environmental Monitoring:-**

The first technology layer is the Internet of Things. IoT environmental systems combine sensors, communications and software so that measurements can be captured at multiple locations and transmitted automatically. Construction-specific research has demonstrated applications for particulate matter, gases, meteorological variables and noise. Kim et al. (2021) showed the feasibility of distributed particulate monitoring across construction sites, while Milivojević et al. (2023) used IoT devices to examine PM2.5, PM10, NO2 and meteorological variables during construction operations. The major advantage is temporal resolution: continuous or high-frequency data can show short peaks that periodic monitoring may miss. The major limitation is measurement quality. Low-cost sensing can have strong relative precision while still exhibiting accuracy limitations, meaning such sensors should be used with calibration, co-location and quality-assurance procedures when data may support formal compliance decisions. Edge computing addresses the problem of latency, bandwidth and local reliability. Instead of transmitting every raw value directly to a remote cloud platform, an edge gateway can perform time synchronisation, sensor-health checks, averaging, anomaly screening and local alerting. Xu et al. (2022) integrated edge computing, BIM and predictive models in a construction air-pollution platform, illustrating how local processing can support faster emergency response. For remote Saudi sites or large developments with uneven connectivity, an edge architecture also enables buffering during network interruptions and prevents monitoring failure from becoming dependent on uninterrupted external connectivity.

BIM and GIS provide environmental context. A concentration reading becomes more useful when connected to the location of the sensor, the active work package, the nearest sensitive receptor, prevailing wind direction and the relevant permit condition. BIM can represent work areas, structures and construction activities; GIS can represent larger spatial relationships such as wadis, coastlines, protected zones, residential areas and monitoring stations. Digital twin approaches extend this by synchronising physical measurements with a virtual representation of the project. Wang et al. (2022) demonstrated semantic integration of sensor data with BIM through SensorML, while Kang and Mo (2024) emphasised connectivity and predictability in digital-twin environmental monitoring. For mega-projects, this enables environmental events to be visualised spatially rather than reduced to disconnected spreadsheet values.

AI and machine learning can transform monitoring from descriptive to predictive. Guo et al. (2022) applied LSTM optimisation to PM<sub>2.5</sub> monitoring and prediction, while Tripathi et al. (2024) combined IoT dust monitoring with multiple machine-learning models. Predictive analytics may provide an early-warning capability: for example, a model could estimate the probability of a PM<sub>10</sub> exceedance based on current concentrations, wind speed, humidity and planned earthworks. However, prediction introduces model risk. Algorithms must be validated, retrained as site conditions change and presented with uncertainty. A black-box prediction should not automatically override regulatory measurement protocols or qualified environmental judgement.

UAVs and remote sensing expand monitoring into areas that are difficult to instrument continuously. Drones can collect high-resolution visual, thermal or spectral data over large work fronts, inspect inaccessible locations and support mapping of dust plumes, erosion, habitat disturbance or coastal turbidity. Bakirci (2024) demonstrated drone-based mapping of air-pollutant distributions, and Noh et al. (2024) used RGB UAV imagery to estimate suspended sediment at a coastal construction site. UAV deployment nevertheless requires aviation compliance, safe operating procedures, privacy controls and risk assessment. Zhu et al. (2023) showed that integrating drones into construction creates physical interaction risks that must themselves be managed.

Blockchain and tamper-evident data architectures offer a different capability: trust. Environmental compliance often involves multiple parties with different contractual interests. Zhong et al. (2022) developed a proof-of-concept blockchain architecture for construction environmental monitoring and smart-contract evaluation of pollutant performance. Full blockchain deployment may not be necessary in every project, but the underlying principle is valuable: environmental records should have controlled timestamps, clear provenance, version management and protection against untracked alteration.

The literature therefore points to an integrated stack rather than a single preferred technology. Sensors generate observations; edge systems validate and transmit them; BIM/GIS and digital twins add context; AI predicts or classifies risk; UAVs provide spatial coverage; and secure data governance protects evidence. The management challenge is to combine these elements without creating a technically sophisticated system that is disconnected from regulatory obligations and field response.

**Table 1. Digital technologies and their environmental compliance roles**

| Technology          | Primary function                   | Typical applications                   | Principal value                             | Key limitations                                    |
|---------------------|------------------------------------|----------------------------------------|---------------------------------------------|----------------------------------------------------|
| IoT sensor networks | Continuous multi-point measurement | Air quality, noise, weather, water     | High temporal resolution; early warning     | Calibration drift; power/connectivity; maintenance |
| Edge computing      | Local preprocessing and alerting   | Remote sites; rapid response           | Low latency; resilience during network loss | Configuration control; device security             |
| BIM / GIS           | Spatial and asset context          | Source–receptor mapping; work packages | Links readings to activities and receptors  | Interoperability; model upkeep                     |
| Digital twin        | Live virtual representation        | Integrated programme monitoring        | Contextual visualisation; scenario analysis | Data integration complexity; governance            |
| AI / ML             | Prediction and anomaly detection   | Dust forecasting; source attribution   | Preventive action; pattern recognition      | Model drift; explainability;                       |

|                                  |                               |                                         |                                       |                                        |
|----------------------------------|-------------------------------|-----------------------------------------|---------------------------------------|----------------------------------------|
|                                  |                               |                                         |                                       | validation                             |
| UAV / remote sensing             | Wide-area spatial observation | Coastal turbidity; habitat; dust plumes | Rapid coverage of difficult areas     | Flight rules; weather; privacy; safety |
| Blockchain / tamper-evident logs | Data provenance and trust     | Multi-party compliance records          | Traceability; immutable event history | Complexity; integration overhead       |

### Methodology:-


This paper adopts a structured narrative review and conceptual-framework development method. The objective is not to estimate a pooled effect size but to integrate diverse evidence from construction engineering, environmental monitoring, digital twins, IoT, AI, remote sensing and Saudi regulatory sources into an implementation model. The method is appropriate because the research question is systems-oriented: it asks how technologies and compliance processes should connect rather than whether one specific sensor or algorithm statistically outperforms another.

Academic literature was prioritised from 2021 to 2024, with emphasis on peer-reviewed studies that addressed real-time environmental sensing, construction-site pollution, digital twins, BIM-integrated monitoring, AI-based prediction, UAV monitoring or data traceability. Official Saudi sources were used to establish the current compliance context, including NCEC material on environmental-quality monitoring, environmental reporting services, construction dust controls and risk-based inspections, together with Vision 2030 reporting. ISO 14001:2026 was used as the management-system reference point. Older literature was not relied upon where recent studies addressed the same technology more directly.

The synthesis was performed in four stages. First, technologies were coded according to their principal function: sensing, connectivity, spatial contextualisation, analytics, remote observation or evidence assurance. Second, compliance functions were coded as monitoring, threshold evaluation, notification, corrective action, verification and reporting. Third, cross-cutting implementation risks were identified, including calibration, missing data, cybersecurity, interoperability, model uncertainty, role ambiguity and over-reliance on low-cost sensors. Fourth, the technology and compliance codes were integrated into a layered framework designed for project implementation.

Eighteen selected peer-reviewed studies formed the core technology synthesis. The technology categories are non-exclusive because a single study may combine IoT, AI, BIM and digital-twin methods. The resulting coding is presented only as a descriptive synthesis of the selected literature, not as a bibliometric representation of the entire research field. No fabricated project measurements, survey responses or performance improvements are used in this paper. Where implementation metrics are proposed, they are identified as suggested key performance indicators for future validation.

The framework was evaluated conceptually against five design criteria: regulatory relevance, technical feasibility, scalability to mega-project conditions, traceability of evidence and compatibility with an ISO 14001-style EMS. This produces a normative framework that can be empirically tested through expert review, case-study deployment and longitudinal data analysis in future research.



**Figure 1. Technology emphasis in the selected peer-reviewed literature used for the conceptual synthesis. Categories are non-exclusive.**

#### **Smart Environmental Monitoring and Compliance Framework (SEMCF):-**


The proposed SEMCF has six integrated layers: sensing; edge and connectivity; data integration; analytics; compliance control; and governance and assurance. The architecture is shown in Figure 1. The framework is deliberately modular because environmental risks vary by project phase and location. A marine package may emphasise turbidity and water quality; a major earthworks package may emphasise dust, noise and runoff; an operational transport asset may emphasise air quality, energy, emissions and noise. The sensing layer converts environmental conditions into observations. It can include reference-grade instruments, low-cost distributed sensors, weather stations, acoustic monitors, water-quality probes, smart cameras, UAV imagery, satellite products and manual field measurements. Sensor selection should be risk based. Parameters linked directly to permit limits or potential enforcement action may require higher-grade instrumentation, accredited laboratory analysis or documented equivalency. Lower-cost devices can still be valuable for screening, spatial mapping and early warning if their limitations are formally understood.

The edge and connectivity layer ensures reliable transmission and initial quality control. Every data point should carry a timestamp, sensor identifier, location and data-quality status. Gateways should check whether readings fall within plausible ranges, identify loss of signal, retain data during communication failure and flag overdue calibration. In a mega-project context, network architecture may combine local wireless systems, cellular connectivity and project fibre or 5G infrastructure. Redundancy is important because environmental evidence should not disappear when a single communications pathway fails. The data-integration layer connects environmental measurements with spatial and operational information. This is where BIM, GIS and digital-twin capabilities generate practical value. A dust exceedance should be linked to the work zone, haul route, crusher, batching plant or excavation activity occurring at the time. A water-quality change should be linked to drainage catchments, dewatering outlets, rainfall, upstream conditions and nearby works. This contextual layer supports source investigation and makes dashboards more meaningful for managers who need to decide what action to take.


The analytics layer has three levels. Level 1 applies deterministic rules: thresholds, rolling averages, rate-of-change alarms and permit conditions. Level 2 applies diagnostic analytics to identify probable sources or correlations. Level 3 applies predictive models to estimate future conditions or exceedance probability. Moving from Level 1 to Level 3 should increase—not reduce—the need for governance. Predictive models should have documented training data, validation metrics, retraining triggers and human approval rules. A model warning can support preventive action, but a model should not silently redefine a regulatory limit.

The compliance-control layer converts information into accountability. Each regulated parameter should have a digital compliance register containing the relevant legal or permit requirement, monitoring method, frequency, trigger level, responsible person, required action, verification step and reporting obligation. When a trigger is reached, the system should send the alert to named roles rather than a generic dashboard. Escalation should depend on severity: advisory alerts may prompt inspection or preventive controls, while significant exceedances may require activity modification, temporary suspension, incident notification or regulator engagement according to applicable procedures.

The governance and assurance layer protects credibility. It includes sensor calibration, laboratory interfaces, cybersecurity, access rights, data retention, version control, competency requirements and internal audit. It also defines ownership of the system. Environmental teams should own the compliance logic; digital teams should manage the technology platform; construction teams should own operational response; and senior management should review unresolved or recurring nonconformities. Where regulatory reporting requires licensed environmental service providers, the digital platform should support those providers rather than bypass them. The core design principle is closed-loop control. Monitoring is not complete when a dashboard displays a red icon. The loop closes only after the condition is validated, action is taken, effectiveness is verified, the event is documented and the risk register or control plan is updated where necessary. Figure 2 presents this operating loop.



**Figure 2. Proposed integrated Smart Environmental Monitoring and Compliance Framework (SEMCF).**



**Figure 3. Closed-loop digital environmental compliance process from monitoring to continual improvement.**

#### **Application to Priority Environmental Risks:-**

Dust and air quality are the most immediate application in the current Saudi context because NCEC has already linked qualifying Riyadh construction projects to continuous air-quality monitoring expectations. Smart dust monitoring should combine PM10 and, where relevant, PM2.5 with meteorological data. Wind direction and speed are essential because a high reading without wind context may not reveal whether the project is the source. Sensor networks can be located near emission sources, site boundaries and sensitive receptors, with at least one suitable background or upwind reference where practicable. Predictive models can combine current concentrations, weather forecasts and planned activities to trigger preventive watering, reduced vehicle speeds, stockpile controls or temporary work sequencing changes before an exceedance occurs.

Noise and vibration require similarly contextualised monitoring. Fixed monitors can track continuous levels near receptors, while mobile instruments can be deployed for high-risk activities such as piling, blasting or heavy compaction. The digital platform should link measurements to equipment schedules and approved working hours. Alerts become more useful when they state not only that a threshold is approached but which activity is occurring and which receptor is affected. Wearable or worker-level devices may support occupational monitoring, but community and environmental compliance should remain distinct from occupational exposure requirements.

Water-quality monitoring is particularly important for projects involving dewatering, concrete works, camps, wastewater systems, coastal construction or stormwater discharge. Continuous probes can measure parameters such as pH, conductivity, temperature, dissolved oxygen or turbidity, depending on the context, while laboratory testing remains necessary for parameters that cannot be reliably determined in situ. Smart systems can identify sudden changes and automatically cross-reference them with rainfall, pumping rates or nearby activities. For marine works, UAV and remote-sensing methods may help map sediment plumes beyond the spatial reach of a single probe.

Soil and land contamination monitoring is less continuously sensor-driven but can still benefit from digitalisation. GIS layers can map fuel storage, chemical areas, spill history, contaminated-soil stockpiles and sampling locations. Smart tank-level sensors, leak detection, hydrocarbon detectors and connected inspection records can strengthen prevention. A digital incident map can reveal recurring spill hotspots and guide redesign of storage or traffic

arrangements. Waste monitoring can combine weighbridge data, QR or RFID tracking, contractor records and geospatial information. Although waste is often discussed as a circular-economy topic, illegal dumping, poor hazardous-waste segregation and uncontrolled storage are also environmental compliance risks. Smart monitoring can reconcile quantities generated, stored and transported, flag unusual balances and preserve waste-manifest evidence.

Biodiversity and ecological receptors require a different digital approach. UAV imagery, camera traps, acoustic sensors and satellite data can support habitat surveillance and detect unauthorised encroachment, vegetation loss or changes in sensitive areas. However, ecological monitoring cannot be reduced to automation. Specialist interpretation remains essential, particularly for seasonal species, habitat condition and cumulative effects. Technology should extend ecological observation, not replace field ecology.

Cumulative impacts are where integrated systems can provide their greatest strategic value. Mega-projects contain many simultaneous work fronts, each of which may appear compliant in isolation while collectively creating elevated dust, noise, traffic or water pressure. A central platform can aggregate spatial and temporal data across packages and identify emerging hotspots. This is a fundamental advantage over contractor-by-contractor spreadsheets because it allows the project owner to manage environmental performance at programme scale.

**Table 2. Priority environmental domains and smart-monitoring design**

| Domain            | Indicative parameters/data                          | Monitoring mode                             | Spatial logic                                    | Management response                               |
|-------------------|-----------------------------------------------------|---------------------------------------------|--------------------------------------------------|---------------------------------------------------|
| Air / dust        | PM10, PM2.5, NO2, wind speed/direction              | Continuous + periodic reference checks      | Source, boundary, receptor and background points | Early warning; suppression; work sequencing       |
| Noise / vibration | LAeq, maxima, PPV where relevant                    | Continuous or activity-based                | Sensitive receptors and high-risk work fronts    | Schedule control; equipment mitigation            |
| Water / discharge | pH, turbidity, EC, DO, temperature + lab parameters | Continuous probes + laboratory confirmation | Outfalls, dewatering points, receiving waters    | Containment; treatment adjustment; stop discharge |
| Soil / spills     | Tank levels, leak detection, mapped incidents       | Continuous detection + inspections          | Fuel/chemical storage and transfer zones         | Isolation; spill response; remediation            |
| Waste             | Weights, manifests, hazardous stream tracking       | Transaction/event based                     | Generation, storage, transport, destination      | Segregation; contractor verification              |
| Biodiversity      | Imagery, acoustic/camera data, habitat change       | Seasonal / event / periodic                 | Sensitive habitats and exclusion zones           | Work exclusion; restoration; specialist review    |

#### **Data Quality, Calibration and Regulatory Defensibility:-**

The credibility of smart environmental monitoring depends on measurement quality. Digital systems can generate millions of data points, but volume is not equivalent to evidence. Low-cost sensors may drift, respond to temperature or humidity, require site-specific correction or exhibit differences between units. Therefore, every project should define a measurement quality hierarchy. Reference or regulatory-grade instruments should anchor the system; distributed lower-cost sensors can provide spatial density; and laboratory analysis should confirm parameters that require formal analytical methods.

Calibration must be treated as a controlled compliance process. The platform should record calibration date, certificate, due date, responsible provider and instrument status. Data from a sensor that is out of calibration should be automatically flagged and should not be presented with the same evidentiary status as validated data. Co-location campaigns can compare low-cost devices against reference equipment and support correction factors, but those factors should be documented, version-controlled and periodically reassessed.

Data completeness is another key parameter. A dashboard can look operational while silently losing data. Monitoring KPIs should therefore include uptime, data capture rate, communication loss, invalid readings and time-to-repair. Missing data during a high-risk construction activity should trigger investigation because absence of evidence is itself an operational concern. Edge buffering and redundant communication routes can reduce this risk. Cybersecurity is part of environmental assurance because compromised sensors or altered thresholds can affect compliance decisions. Access to threshold libraries, permit registers and calibration settings should be role-based. Administrative changes should be logged. Data transmitted from sensors should be authenticated where feasible, and project cybersecurity teams should include environmental monitoring assets within vulnerability and patch-management processes. Environmental systems connected to wider project networks should not become unmanaged entry points.

Human oversight remains essential. Automated alerts should be designed to reduce cognitive load, not create alarm fatigue. Thresholds should be tiered and linked to clear response expectations. A minor transient excursion may require validation, whereas a sustained exceedance may require immediate operational control and escalation. Environmental professionals should have authority to interpret anomalous readings in context and to override automated classifications when justified, with the reason documented.

Regulatory defensibility requires a clear chain of custody for digital evidence. The system should preserve raw data, processed values, analytical rules and changes to configuration. Where reports are submitted to NCEC or used to demonstrate permit compliance, the method should align with applicable regulatory guidance and provider-licensing requirements. This approach is consistent with the logic of ISO 14001:2026: monitoring is valuable when it supports compliance evaluation and continual improvement through controlled information.

**Table 3. Example tiered digital alert and escalation model**

| Tier        | Condition                                                        | System response                                                          | Accountable role                                   | Required closure evidence                              |
|-------------|------------------------------------------------------------------|--------------------------------------------------------------------------|----------------------------------------------------|--------------------------------------------------------|
| Advisory    | Approaching internal trigger or adverse trend                    | Automated notification; field check                                      | Environmental supervisor                           | Validated status and preventive action                 |
| Action      | Internal trigger exceeded or rapid deterioration                 | Immediate control and investigation                                      | Package environmental manager + construction lead  | Control effectiveness verified                         |
| Significant | Permit/regulatory threshold exceeded or credible pollution event | Escalate; modify/stop activity as required; incident process             | Project environmental manager + project leadership | Cause, correction and notification decision recorded   |
| Critical    | Major release, repeated exceedance, sensitive receptor impact    | Emergency response; senior escalation; regulator interface as applicable | Project director / emergency roles                 | Formal closeout, lessons learned and management review |

#### **Implementation Roadmap for Saudi Mega-Projects:-**

Implementation should proceed in phases rather than through a single technology procurement. Phase 1 is compliance mapping. The project identifies every environmental permit condition, regulatory monitoring requirement, contractual environmental commitment and internal risk-control requirement. These are converted into a digital compliance register with parameters, locations, frequencies, thresholds, responsibilities and evidence requirements. Phase 2 is monitoring design. Environmental risks are mapped spatially and temporally to determine what should be monitored continuously, periodically or through event-based campaigns. Sensor locations are selected using source–pathway–receptor logic. Connectivity, power, calibration access and physical protection are considered at design stage. A mega-project may require a hierarchy of central stations, local work-package sensors and mobile monitoring units rather than one uniform device type.

Phase 3 is platform integration. Environmental data should be connected to project GIS, BIM or a digital twin where these systems exist. Integration should focus on decision usefulness, not technological novelty. The first priority is to make environmental readings spatially intelligible and linked to work activities. Only after this foundation is stable should advanced AI models or automated source attribution be added. Phase 4 is controlled automation. Thresholds and alert logic are tested against historical or pilot data. Escalation rules are agreed with construction and project leadership. Automated notifications should include the parameter, value, threshold, location, trend, weather context, likely source and required response. The system should create a response ticket so that an alert cannot disappear without closure. Phase 5 is assurance and scaling. The project audits calibration, data completeness, response times, false alarms, unresolved exceedances and user behaviour. Successful monitoring packages can then

be scaled to additional work fronts. Lessons from one project can inform standard owner requirements across a portfolio, creating a consistent digital environmental governance model. Procurement strategy is important throughout. Technology vendors should be evaluated not only on sensor specifications but also on interoperability, calibration support, data ownership, export formats, cybersecurity, service continuity and the ability to integrate with regulatory reporting. Contracts should state who owns environmental data and how long it must be retained. Proprietary lock-in should be avoided where it would prevent migration or independent audit. The project should also establish a digital environmental governance committee or equivalent cross-functional forum. Environmental, construction, digital, HSE, legal, cybersecurity and project-controls representatives can review system performance and unresolved data issues. This is particularly valuable where digital platforms cross organisational boundaries between the owner, PMC, consultants and contractors.

Suggested implementation KPIs include percentage of high-risk sources under continuous monitoring, sensor uptime, proportion of devices within calibration, median time from exceedance to acknowledgement, median time to corrective action, percentage of alerts closed with verification, repeat-exceedance rate, data completeness, number of manually altered records and percentage of required monitoring reports generated from validated data. These KPIs should be piloted and refined rather than assumed to be universally applicable.

**Table 4. Suggested implementation KPIs for future project validation**

| KPI group        | Example metric                                                               | Purpose                                                            |
|------------------|------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Sensor assurance | % devices in calibration; data completeness; uptime                          | Shows whether monitoring evidence is technically dependable        |
| Detection        | Median time from environmental change to alert                               | Measures monitoring responsiveness                                 |
| Response         | Median time from alert to acknowledgement / control                          | Measures operational integration                                   |
| Effectiveness    | % alerts closed with verified control effectiveness                          | Prevents administrative closure without environmental verification |
| Recurrence       | Repeat exceedance rate by source/work package                                | Identifies weak root-cause control                                 |
| Governance       | Number of unauthorised configuration changes / unresolved data-quality flags | Measures integrity of the digital compliance system                |
| Reporting        | % required monitoring reports generated from validated data                  | Links digital platform to formal compliance obligations            |

### Discussion:-

The analysis indicates that smart environmental monitoring can materially strengthen environmental management in Saudi mega-projects, but only when it is designed as a compliance operating system rather than a collection of devices. The strongest technological pattern in the reviewed literature is convergence. IoT provides continuous sensing, digital twins and BIM add context, AI adds prediction, UAVs extend spatial coverage and secure data architectures strengthen traceability. Each technology addresses a different weakness of conventional monitoring. Saudi Arabia is particularly well positioned for this convergence because its mega-projects are generally new-build developments with substantial digital infrastructure and centralised owner governance. New projects can specify sensor-ready monitoring stations, data standards, digital submission requirements and integrated control rooms from the outset. Retrofitting fragmented legacy projects is usually more difficult.

The current NCEC direction toward real-time dust monitoring and risk-based inspection strengthens the institutional case for digital compliance systems. Nevertheless, technology can create new forms of risk. The first is false confidence. A high-density network of poorly calibrated sensors may provide more data but worse evidence. The second is algorithmic opacity. Predictive models may perform well under historical conditions and poorly when construction activities or weather patterns change. The third is fragmentation: contractors may deploy incompatible platforms that prevent programme-level analysis. The fourth is cybersecurity and data-governance exposure. The fifth is behavioural: if site teams see monitoring as surveillance imposed by the environmental department, alerts may be ignored or controls bypassed.

For these reasons, environmental monitoring should remain risk based. Not every parameter needs a sensor, and not every sensor needs AI. The value of a digital tool depends on the decision it improves. A simple automatic threshold alarm with a reliable calibrated monitor may be more useful than a complex predictive model that users do not trust. Technology maturity should therefore follow environmental need. The framework also changes the role of the environmental professional. Instead of spending most of the time collecting and compiling data, practitioners can increasingly focus on system design, risk interpretation, investigation and control effectiveness. This does not reduce the need for professional expertise; it increases the importance of understanding data quality, digital systems and regulatory evidence. Environmental competency frameworks for Saudi mega-projects may therefore need to expand toward digital environmental assurance.

At regulator level, standardisation could generate significant benefits. Common data schemas, approved monitoring interfaces and clearer guidance on the evidentiary status of continuous sensors would reduce inconsistency across projects. NCEC's electronic services and current technology-supported monitoring indicate a foundation on which such standards can develop. Future regulatory innovation could include machine-readable permit conditions, automated submission interfaces and risk-based inspection models informed by verified continuous data. The proposed SEMCF is deliberately not presented as validated. Its performance should be tested through multi-case research across different Saudi project types. Quantitative studies could compare incident detection time, exceedance duration, corrective-action closure and reporting efficiency before and after implementation. Expert studies could assess framework completeness and regulatory fit. Longitudinal research could evaluate whether predictive alerts reduce exceedances rather than simply improve documentation. These empirical steps are necessary before claiming causal performance benefits.

### **Conclusion:-**

Saudi mega-projects are entering a period in which environmental compliance, digital transformation and large-scale construction increasingly intersect. Current NCEC practice demonstrates that real-time monitoring and technology-supported oversight are becoming operational elements of environmental governance. This makes smart monitoring a practical compliance issue, not only a research topic. This paper developed a Smart Environmental Monitoring and Compliance Framework that integrates sensing, edge computing, BIM/GIS, digital twins, AI, UAVs and secure data governance with permit conditions, risk controls, alerts, corrective action and reporting. The central finding is that technology creates environmental value only when the complete control loop is designed. Measurements must be reliable, contextualised and linked to accountable action. Calibration, data quality, cybersecurity, threshold governance and human professional judgement are therefore as important as sensor density or analytical sophistication.

For Saudi mega-projects, the most promising near-term applications are continuous dust and air-quality monitoring, noise and vibration surveillance, water-quality early warning, digital waste traceability, remote ecological observation and programme-level cumulative-impact dashboards. A phased implementation beginning with compliance mapping and monitoring design is preferable to technology-first procurement. The framework provides a foundation for empirical research and project implementation. Future studies should validate it with Saudi regulators, project owners, environmental consultants and contractors; test it on active mega-projects; and quantify the effect on detection time, response performance and compliance outcomes. Such evidence would allow smart environmental monitoring to progress from promising digital capability to a mature component of Saudi Arabia's sustainable infrastructure governance under Vision 2030.

### **Limitations and Future Research:-**

This study is a conceptual review and framework-development paper. It does not use primary monitoring data from a named Saudi mega-project and therefore cannot quantify the magnitude of performance improvement attributable to the SEMCF. The selected academic literature is intentionally multidisciplinary and targeted rather than exhaustive, and the descriptive technology coding should not be interpreted as a formal bibliometric analysis of the entire field.

Future research should proceed in three directions. First, a Delphi or structured expert-validation study involving NCEC-licensed environmental consultants, mega-project owners, contractors, digital-system specialists and regulators can test the relevance and completeness of the proposed layers. Second, project case studies can evaluate technical performance, including sensor accuracy, data completeness, false-alarm rates, system uptime and integration with BIM/GIS platforms. Third, longitudinal comparative research can evaluate management outcomes

such as exceedance duration, response time, recurrence rate and the quality of regulatory reporting before and after implementation.

A further research priority is evidentiary equivalence. Studies should distinguish between sensors suitable for operational early warning and measurement methods accepted for formal compliance. This distinction is important because digitalisation should increase regulatory confidence rather than blur the boundary between indicative and reference measurements. Research on cybersecurity, data ownership, machine-readable permit conditions and standardised environmental data models would also support scaling across Saudi project portfolios.

## References:-

1. Bakirci, M. (2024). A drone-based approach to enhance spatial insight into surrounding air pollutant distributions for healthier indoor environments. *Journal of Building Engineering*, 87, 109023. <https://doi.org/10.1016/j.jobbe.2024.109023>
2. Guo, X., Wang, Y., Mei, S., Shi, C., Liu, Y., Pan, L., Li, K., Wang, J., Zhong, Z., & Dong, M. (2022). Monitoring and modelling of PM<sub>2.5</sub> concentration at subway station construction based on IoT and LSTM algorithm optimization. *Journal of Cleaner Production*, 360, 132179. <https://doi.org/10.1016/j.jclepro.2022.132179>
3. International Organization for Standardization (ISO). (2026). ISO 14001:2026 Environmental management systems — Requirements with guidance for use. Geneva: ISO.
4. Kang, T. W., & Mo, Y. L. (2024). A comprehensive digital twin framework for building environment monitoring with emphasis on real-time data connectivity and predictability. *Developments in the Built Environment*, 17, 100309. <https://doi.org/10.1016/j.dibe.2023.100309>
5. Kim, H., Tae, S., Zheng, P., Kang, G., & Lee, H. (2021). Development of IoT-Based Particulate Matter Monitoring System for Construction Sites. *International Journal of Environmental Research and Public Health*, 18(21), 11510. <https://doi.org/10.3390/ijerph182111510>
6. Milivojević, L., Mrazovac Kurilić, S., Božilović, Z., Koprivica, S., & Krčadinac, O. (2023). Study of Particular Air Quality and Meteorological Parameters at a Construction Site. *Atmosphere*, 14(8), 1267. <https://doi.org/10.3390/atmos14081267>
7. National Center for Environmental Compliance (NCEC). (2024). Guidance for preparing and implementing environmental monitoring reports. Kingdom of Saudi Arabia.
8. National Center for Environmental Compliance (NCEC). (2026a). Special requirements for construction projects and dust-control compliance in Riyadh. Kingdom of Saudi Arabia, 19 February 2026.
9. National Center for Environmental Compliance (NCEC). (2026b). More than 11,000 environmental inspection rounds implemented during the first quarter of 2026. Kingdom of Saudi Arabia, 23 April 2026.
10. National Center for Environmental Compliance (NCEC). (2026c). Environmental monitoring reports service requirements. Kingdom of Saudi Arabia.
11. National Center for Environmental Compliance (NCEC). (n.d.-a). Monitoring environmental quality. Kingdom of Saudi Arabia.
12. National Center for Environmental Compliance (NCEC). (n.d.-b). Overview and mandate. Kingdom of Saudi Arabia.
13. Noh, H., Kwon, S., Park, Y. S., & Woo, S.-B. (2024). Application of RGB UAV imagery to sea surface suspended sediment concentration monitoring in coastal construction site. *Applied Ocean Research*, 147, 103940. <https://doi.org/10.1016/j.apor.2024.103940>
14. Omrany, H., Al-Obaidi, K. M., Husain, A., & Ghaffarianhoseini, A. (2023). Digital Twins in the Construction Industry: A Comprehensive Review of Current Implementations, Enabling Technologies, and Future Directions. *Sustainability*, 15(14), 10908. <https://doi.org/10.3390/su151410908>
15. Pal, A., Lin, J. J.-C., Hsieh, S.-H., & Golparvar-Fard, M. (2023). Automated vision-based construction progress monitoring in built environment through digital twin. *Developments in the Built Environment*, 16, 100247. <https://doi.org/10.1016/j.dibe.2023.100247>
16. Saudi Vision 2030. (2026). Vision 2030 Annual Report 2025. Kingdom of Saudi Arabia.
17. Su, S., Zhong, R. Y., Jiang, Y., Song, J., Fu, Y., & Cao, H. (2023). Digital twin and its potential applications in construction industry: State-of-art review and a conceptual framework. *Advanced Engineering Informatics*, 57, 102030. <https://doi.org/10.1016/j.aei.2023.102030>
18. Tripathi, A. K., Aruna, M., Parida, S., Nandan, D., Elumalai, P. V., Prakash, E., Lalvani, J. S. C. I. J. R., & Rao, K. S. (2024). Integrated smart dust monitoring and prediction system for surface mine sites using IoT and machine learning techniques. *Scientific Reports*, 14, 7587. <https://doi.org/10.1038/s41598-024-58021-x>

19. Tuhaise, V. V., Tah, J. H. M., & Abanda, F. H. (2023). Technologies for digital twin applications in construction. *Automation in Construction*, 152, 104931. <https://doi.org/10.1016/j.autcon.2023.104931>
20. Wang, T., Gan, V. J. L., Hu, D., & Liu, H. (2022). Digital twin-enabled built environment sensing and monitoring through semantic enrichment of BIM with SensorML. *Automation in Construction*, 144, 104625. <https://doi.org/10.1016/j.autcon.2022.104625>
21. Xu, Z., Ran, Y., & Rao, Z. (2022). Design and integration of air pollutants monitoring system for emergency management in construction site based on BIM and edge computing. *Building and Environment*, 211, 108725. <https://doi.org/10.1016/j.buildenv.2021.108725>
22. Yevu, S. K., Owusu, E. K., Chan, A. P. C., Sepasgozar, S. M. E., & Kamat, V. R. (2023). Digital twin-enabled prefabrication supply chain for smart construction and carbon emissions evaluation in building projects. *Journal of Building Engineering*, 78, 107598. <https://doi.org/10.1016/j.jobbe.2023.107598>
23. Zhong, B., Guo, J., Zhang, L., Wu, H., Li, H., & Wang, Y. (2022). A blockchain-based framework for on-site construction environmental monitoring: Proof of concept. *Building and Environment*, 217, 109064. <https://doi.org/10.1016/j.buildenv.2022.109064>
24. Zhu, Z., Jeelani, I., & Gheisari, M. (2023). Physical risk assessment of drone integration in construction using 4D simulation. *Automation in Construction*, 156, 105099. <https://doi.org/10.1016/j.autcon.2023.105099>